

LINEAR TECHNOLOGY MATERIALS DECLARATION

ltc2620cufd#pbf

(Engineering Calculation)

QFN 4mm X 5mm Exp. Pad

(printed on: 2020-07-11 21:56:42)

TOTAL MASS (g) : 0.05221

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.003774 | 1000000 | 72284.7109375 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.019997 | 975000 | 383009.40625 | | |
| | | Iron (Fe) | 7439-89-6 | 0.000492 | 24000 | 9423.4453125 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000006 | 300 | 114.920059204 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000014 | 700 | 268.146789551 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.020509 | 1000000 | 392815.90625 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.000227 | 1000000 | 4351.79248047 | | |
| | | External Plating Total: | | | | 0.000227 | 1000000 | 4351.79248047 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000498 | 1000000 | 9538.36425781 | | |
| Internal Plating Total: | | | | 0.000498 | 1000000 | 9538.36425781 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.001436 | 750000 | 27504.1992188 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000479 | 250000 | 9174.45117188 | | |
| Die Attach Total: | | | | 0.001915 | 1000000 | 36678.6523438 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.003244 | 130000 | 62133.4414062 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.021457 | 860000 | 410973.28125 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000250 | 10000 | 4788.3359375 | | |
| | | Encapsulation Total: | | | | 0.024951 | 1000000 | 477895.0625 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000336 | 1000000 | 6435.5234375 | | |
| | | | | | TOTAL MASS (g) : | 0.05221 | | |