

CERTIFICATE OF COMPLIANCE

Certificate Number 20181103-E139109
Report Reference E139109-A6046-UL
Issue Date 2018-NOVEMBER-03

Issued to: XP POWER L L C
15641 RED HILL AVE, SUITE 100
TUSTIN CA 92780

**This certificate confirms that
representative samples of**

Component - Power Supplies for Use in Audio/Video,
Information and Communication Technology Equipment
Switching Power Supply, Models: 10003831, 10006770,
ECM60US12-XB0324, ECM60US24-C, ECM40USXX,
ECM60USXX, ECC40USXX, ECC60USXX;
Where XX can be any number between 05 and 48
designating the output voltage. May be followed by 3X5.

Have been investigated by UL in accordance with the
component requirements in the Standard(s) indicated on
this Certificate. UL Recognized components are incomplete
in certain constructional features or restricted in
performance capabilities and are intended for installation in
complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 62368-1 and CAN/CSA C22.2 No. 62368-1-14,
Audio/Video, Information and Communication Technology
Equipment Part 1: Safety Requirements

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified
and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



UL TEST REPORT AND PROCEDURE

Standard:	UL 62368-1, 2nd Ed, 2014-12-01 (Audio/video, information and communication technology equipment Part 1: Safety requirements) CAN/CSA C22.2 No. 62368-1-14, 2nd Ed (Audio/video, information and communication technology equipment Part 1: Safety requirements)
Certification Type:	Component Recognition
CCN:	QQJQ2, QQJQ8 (Power Supplies for Use in Audio/Video, Information and Communication Technology Equipment)
Complementary CCN:	N/A
Product:	Switching Power Supply
Model:	10003831 10006770 ECM60US12-XB0324 ECM60US24-C ECM40USXX ECM60USXX ECC40USXX ECC60USXX Where XX can be any number between 05 and 48 designating the output voltage. May be followed by 3X5.
Rating:	Models ECM40USXX, ECC40USXX, 10003831: INPUT ~100 - 240VAC 50/60Hz 1A Models ECM60USXX, ECC60USXX, 10006770, ECM60US12-XB0324, ECM60US24-C: INPUT ~100 - 240VAC 50/60HZ 1.5A OUTPUT: See Model Differences for details.
Applicant Name and Address:	XP POWER L L C 15641 RED HILL AVE, SUITE 100 TUSTIN CA 92780 UNITED STATES

This is to certify that representative samples of the products covered by this Test Report have been investigated in accordance with the above referenced Standards. The products have been found to comply with the requirements covering the category and the products are judged to be eligible for Follow-Up Service under the indicated Test Procedure. The manufacturer is authorized to use the UL Mark on such products which comply with this Test Report and any other applicable requirements of UL LLC ('UL') in accordance with the Follow-Up Service Agreement. Only those products which properly bear the UL Mark are considered as being covered by UL's Follow-Up Service under the indicated Test Procedure.

The applicant is authorized to reproduce the referenced Test Report provided it is reproduced in its entirety.

UL authorizes the applicant to reproduce the latest pages of the referenced Test Report consisting of the first page of the Specific Technical Criteria through to the end of the Conditions of Acceptability.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL.

Prepared By: Adam Tangocci / Project Handler Reviewed By: Gregory Ray / Reviewer

Supporting Documentation

The following documents located at the beginning of this Procedure supplement the requirements of this Test Report:

A. Authorization - The Authorization page may include additional Factory Identification Code markings.

B. Generic Inspection Instructions -

- i. Part AC details important information which may be applicable to products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of this Test Report.
- ii. Part AE details any requirements which may be applicable to all products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of each Test Report.
- iii. Part AF details the requirements for the UL Certification Mark which is not controlled by the technical standard used to investigate these products. Products are permitted to bear only the Certification Mark(s) corresponding to the countries for which it is certified, as indicated in each Test Report.

Product Description

Models covered in this report are component power supply intended for use in Information Technology Equipment. Units are intended for use with Class I or Class II end-products.

Model Differences

All Models are identical, except for output ratings, minor differences in the secondary circuit components, heat-sink and the number of turns of secondary winding in the Isolation Transformer (T1).

The difference between Series ECC/ECM40/60 is model designation. The difference between Model 10003831 and the ECM/ECC Series is the heat-sink.

Model 10006770 is identical to ECM60US12 except for output ratings.

Model ECM60US12-XB0324 is identical to ECM60US12.

Model ECM60US24-C is identical to Model ECM60US24 except for chassis cover.

Output Ratings:

ECM40US05 4.1-6VDC 8.0A 40W

ECM40US07 6.1-8VDC 5.7A 40W

ECM40US09 8.1-10VDC 4.4A 40W

ECM40US12 10.1-13.5VDC 3.5A 40W

ECM40US15 13.6-17VDC 2.7A 40W

ECM40US18 17.1-21VDC 2.2A 40W

ECM40US24 21.1-26VDC 1.7A 40W

ECM40US28 26.1-31VDC 1.4A 40W

ECM40US33 31.1-33VDC 1.2A 40W

ECM40US36 33.1-42VDC 1.1A 40W

ECM40US48 42.1-54VDC 0.9A 40W

ECM60US05 4.1-6VDC 12.0A 60W

ECM60US07 6.1-8VDC 8.6A 60W

ECM60US09 8.1-10VDC 6.7A 60W

ECM60US12 10.1-13.5VDC 5.0A 60W

ECM60US15 13.6-17VDC 4.0A 60W

ECM60US18 17.1-19.9VDC 3.3A 60W

ECM60US20 20.0-21.0VDC 3.0A 60W

ECM60US24 21.1-26VDC 2.5A 60W

ECM60US28 26.1-31VDC 2.14A 60W

ECM60US33 31.1-33VDC 1.8A 60W

ECM60US36 33.1-42VDC 1.6A 60W

ECM60US48 42.1-54VDC 1.25A 60W

10003831: 5VDC 6A 30W

10006770: 12.5 VDC 4.8 A

ECM60US12-XB0324: 12 VDC 5.0 A

ECM60US24-C: 24 VDC 2.5A

Test Item Particulars

Classification of use by	Ordinary person
Supply Connection	AC Mains ES1
Supply % Tolerance	+10%/-10%
Supply Connection – Type	For building-in
Considered current rating of protective device as part of building or equipment installation	20 A; building;
Equipment mobility	for building-in
Over voltage category (OVC)	OVC II OVC II
Class of equipment	Not Classified
Access location	N/A
Pollution degree (PD)	PD 2
Manufacturer's specified maximum operating ambient	50°C at 100% rated output; 70°C at 50% rated output; 80°C at 50% rated output with 5cfm fan. °C
IP protection class	IPX0
Power Systems	TN
Altitude during operation (m)	5000 m
Altitude of test laboratory (m)	2000 m or less
Mass of equipment (kg)	0.25

Technical Considerations

- The product was submitted and evaluated for use at the maximum ambient temperature (T_{ma}) permitted by the manufacturer's specification of : 50°C at 100% rated output; 70°C at 50% rated output; 80°C at 50% rated output with 5cfm fan.
- The product is intended for use on the following power systems : TN
-
- The equipment disconnect device is considered to be : To be determined in the end-product.
- Required Clearances have been adjusted by multiplying the clearance at sea level by a factor of 1.48 for operating at an altitude of 5000 meters. The correction factor is based on barometric pressure of 70kPa. If the calculated Clearance exceeded the Creepage, the Creepage was adjusted to the value of clearance.
- Power supplies covered by this report were evaluated for both Class I and Class II (double insulated). Double insulated symbol is optionally provided. Earthing symbol may only be provided for Class I power supplies.

Engineer Conditions of Acceptability

For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC. When installed in an end-product, consideration must be given to the following:

- The following product-line tests are conducted for this product : Electric Strength
-
- The following output circuits are at ES1 energy levels : All Outputs
- The following output circuits are at PS3 energy levels : All Outputs
- The maximum investigated branch circuit rating is : 20 A
-
- The investigated Pollution Degree is : 2
-
- Proper bonding to the end-product main protective earthing termination is : Required (Class I)
- An investigation of the protective bonding terminals has : Not been conducted
-
- The following input terminals/connectors must be connected to the end-product supply neutral : AC N
- The following end-product enclosures are required : Mechanical, Fire, Electrical
- The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation system with the indicated rating greater than Class A (105°C) : T1 (Class F, 155°C) and/or L1 (min. 130°C)
- The power supply was evaluated to be used at altitudes up to : "5000 m"
-
- When installed in a Class I end product, the power supply shall be mounted in a manner that provides the minimum required Clearance between the primary side of power supply and protectively earthed accessible conductive parts.
- When installed in a Class II end product, the power supply shall be mounted on insulating posts in a manner that provides the minimum required Clearance between the power supply and any accessible conductive parts.
- Heatsinks are floating and considered live. They should not be accessible in the end-product.
- A suitable main disconnect device shall be provided in the end product.
- The power supplies covered by this report have a fuse in the neutral of the primary circuit. The need for a marking to warn a service person of the hazards associated with double pole/neutral fusing shall be considered in the end product.
- Consideration to repeating the Touch Current test should be given in the end-product evaluation.
- The power supplies in this report have been subject to Capacitance Discharge testing. Additionally, all associated component safeguards have been assessed to the applicable requirement in Annex G.10. Additional testing should not be needed if directly connected to mains e.g. using an appliance inlet, wiring terminals, etc.

Additional Information

Marking Plate is representative of all models.

This report is based on a previous evaluation to IEC 60950-1:2005 (2nd Ed.), Am1:2009 + Am2:20013 under CBTR Ref. No. E139109-A4-CB-5 including Amendments, CBTC Ref. No. US-25824-UL, and US-25824-A1-UL. Based on the previously conducted performance testing, only the tests conducted as part of this investigation were considered necessary.

The following tests were conducted under CTDP SMT/CTF Stage 3 to IEC 60950-1 E2+A1+A2 at XP POWER LLC, 15641 RED HILL AVE, SUITE 100, TUSTIN , CA 92780, USA:

- Input: Single-Phase (1.6.2)
- Capacitance Discharge (2.1.1.7)
- SELV Reliability Test Including Hazardous Voltage Measurements (2.2.2, 2.2.3, 2.2.4, Part 22 6.1)
- Humidity (2.9.1, 2.9.2, 5.2.2)
- Determination of Working Voltage; Working Voltage Measurement (2.10.2)
- Heating (4.5.1, 1.4.12, 1.4.13)
- Ball Pressure (4.5.5, 4.5)
- Electric Strength (5.2.2)
- Component Failure (5.3.1, 5.3.4, 5.3.7)
- Abnormal Operation (5.3.1 - 5.3.9)
- Transformer Abnormal Operation (5.3.3, 5.3.7b, Annex C.1)
- Power Supply Output Short-Circuit/Overload (5.3.7)

The following additional tests were conducted on a sample of model ECM60US12 in accordance with IEC 62368-1:2014 (Second Edition) at XP POWER LLC, 15641 RED HILL AVE, SUITE 100, TUSTIN, CA 92780 USA:

- Electric Strength Test (5.4.9)
- Prospective Touch Voltage and Touch Current Measurement (5.7)

Additional Standards

The product fulfills the requirements of: EN 62368-1:2014 + A11:2017

Markings and Instructions

Clause Title	Marking or Instruction Details
Equipment identification marking – Manufacturer identification	Listees or Recognized companys name, Trade Name, Trademark or File Number
Equipment identification marking – model identification	Model Number
Equipment rating marking – ratings	"Input Ratings (voltage, frequency/dc, current/power)", "Output Ratings (voltage, frequency/dc, current/power)"
Warning to service personnel	"CAUTION: Double pole, neutral fusing. Disconnect mains before servicing. "/"ATTENTION. Double pôle/fusible sur le neutre. Débrancher l'alimentation avant l'entretien."

Special Instructions to UL Representative

--