



**User Registration**

Register today to create your account on Silabs.com. Your personalized profile allows you to receive technical document updates, new product announcements, "how-to" and design documents, product change notices (PCN) and other valuable content available only to registered users.

<http://www.silabs.com/profile>

<b>Bulletin Date:</b> 3/4/2016		<b>Bulletin Effective Date:</b> 3/4/2016	
<b>Title:</b> Si53307 Rev 1.1 Release DC Mode Operation			
<b>Originator:</b> Murali Chandran		<b>Phone:</b> (512) 464-9278	<b>Dept:</b> Marketing
<b>Customer Contact:</b> Kathy Haggar		<b>Phone:</b> (512) 532-5261	<b>Dept:</b> Sales
<b>Bulletin Details</b>			
<b>Description:</b> Silicon Labs is pleased to announce a Si53307 Data Sheet Change from rev 1.0 to rev 1.1. This datasheet change increases the operating frequency from 1MHz minimum down to DC mode of operation.			
<b>Reason:</b> Si53307 can perform over a wider range of frequencies so data sheet was changed to reflect this.			
<b>Product Identification:</b> Si53307-B-GM Si53307-B-GMR			
This change is considered a minor change which does not affect form, fit, function, quality, or reliability. The information is being provided as a customer courtesy.  Please contact your local Silicon Labs sales representative with any questions about this notification. A list of Silicon Labs sales representatives may be found at <a href="http://www.silabs.com">www.silabs.com</a>			
<b>Customer Actions Needed:</b> This change does not affect current customers. It allows use of the Si53307 in applications that require operation below 1MHz.			